10457 3847

UPnP AV DEVICE INTERWORKING METHOD OF UPnP-BASED NETWORK SYSTEM

TECHNICAL FIELD

5   The present invention relates to a Universal Plug and Play (UPnP)-based network system, and more particularly to, a UPnP AV device interworking method of a UPnP-based network system which allows a UPnP AV device located on a common internet and a UPnP AV device located on a home network to interwork (operate) with each other.

10

BACKGROUND ART

With the advance of information technologies, various IT products such as cellular phones, digital TV sets, PDAs and game machines as well as PCs are connected to each other through a network.   As such a network

15   environment is expanded to houses, a home network gains popularity. Especially, the UPnP gets influential in mutual control and administration of home network devices.

The UPnP is a common protocol prepared by improving a plug and play function, so that various network devices of different standards and

20   specifications can interface each other.   That is, the UPnP allows various home appliances connected to a network, namely, network devices such as a network

1

printer and an internet gateway to network each other on the basis of internet standard technologies such as TCP/IP, HTTP and XML.

In general, the UPnP network system basically includes a UPnP device, a service and a control point (CP), and streams, stores and manages multimedia

5   contents. Here, the UPnP device includes a service and a few sub-devices. For example, a TV/VCR combo device may include a tape transfer service, a tuner service and other built-in devices. The service implies a small-scale control unit on the network system which can model a self state by using state variables. For example, a time model may include a state variable for defining

10   a current time state and a variable for controlling a service.   In addition, the CP implies a controller having functions of sensing and controlling the UPnP devices composing the UPnP.

On the other hand, the UPnP is embodied on the basis of the standards defined by the UPnP forum (http://www.UPnP.org) according to UPnP Device

15   Architecture 1.0 distributed by Microsoft Corporation.

The UPnP forum that leads establishment of the standards of the UPnP devices and services is composed of six working groups. Among the six working groups, the Audio/Video (A/V) working group includes a media server (MS) for providing media data to a home network, a media renderer (MR) for

20   playing back the media data through the home network, and an audio/video control point (AV CP) for controlling the MS and the MR.

Fig. 1 is a block diagram illustrating a general UPnP AV network system.

The operation of the general UPnP device based on the specification of the UPnP AV Device Architecture 1.0 will now be explained with reference to Fig. 1.

5   An AV CP 110 selects contents of an MS 120 by using a user interface (UI), and then selects a target MR 130. The selected contents are transmitted directly from the MS 120 to the MR 130 by out-of-band streaming. Here, the MS 120 provides one or more transfer protocols, and data formats for each contents item. A contents type which the MR 130 can receive is dependent

10   upon a transfer protocol and a data format supported by the MR 130.

The CP 110 activates AVTransport actions (for example, Stop, Pause, FF, REW, Skip and Scan), and controls various rendering (Brightness, Contrast, Volume and Balance) of the MR 130.

However, the UPnP AV network-system based on the UPnP Device

15   Architecture 1.0 is embodied on the presumption that the AV CP, the MS and the MR are located and operated on the home network. Accordingly, the UPnP devices located on a common internet are not allowed to interwork (operate) with each other.

20   **DISCLOSURE OF THE INVENTION**

Therefore, an object of the present invention is to provide a UPnP AV

device interworking method of a UPnP-based network system which allows

UPnP devices to interwork (operate) with each other by transforming a private

address to a public address by Uniformed Resource Identifier (URI) address

transformation, when some of the UPnP devices exist on an internet.

5   To achieve these and other advantages and in accordance with the

purpose of the present invention, as embodied and broadly described herein, in

a UPnP-based network system in which UPnP AV devices are located on a

home network and a common internet, respectively, a UPnP AV device

interworking method of the UPnP-based network system transforms a private

10   address to a public address between the UPnP AV devices located on the home

network and the common internet, respectively.

According to one aspect of the present invention, in a UPnP-based

network system in which UPnP AV devices are located on a home network and

a common internet, respectively, a UPnP AV device interworking method of the

15   UPnP-based network system includes the steps of: obtaining, at a CP controlling

the UPnP AV devices, a URI of contents located on the home network;

transforming, at the CP, a private address of the URI to a public address; and

receiving and playing back, at the UPnP AV device located on the common

internet, predetermined contents by streaming on the basis of the transformed

20   address.

According to another aspect of the present invention, in a UPnP-based

network system in which UPnP AV devices are located on a home network and

a common internet, respectively, a UPnP AV device interworking method of the

UPnP-based network system includes the steps of: obtaining an address of the

UPnP AV device located on the home network; confirming the UPnP AV device

5   located on the common internet by referring to description information; notifying

the address of the UPnP AV device located on the home network to the UPnP

AV device located on the common internet; and playing back contents selected

by the user by transmitting the contents from the UPnP AV device located on the

common internet to the UPnP AV device located on the home network by

10   pushing.

The foregoing and other objects, features, aspects and advantages of the

present invention will become more apparent from the following detailed

description of the present invention when taken in conjunction with the

accompanying drawings.

15

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram illustrating a general UPnP AV network system;

Fig. 2 is a structure diagram illustrating a UPnP AV device control system

in which a CP and an MR are located on a common internet and an MS is

20   located on a home network in accordance with a first embodiment of the present

invention;

Fig. 3 is a structure diagram illustrating a UPnP AV device control system

in which a CP and an MS are located on a home network and an MR is located

on a common internet in accordance with a second embodiment of the present

invention;

5   Fig. 4 is a structure diagram illustrating a UPnP AV device control system

in which a CP and an MS are located on a common internet and an MR is

located on a home network in accordance with a third embodiment of the

present invention; and

Fig. 5 is a structure diagram illustrating a UPnP AV device control system

10   in which a CP and an MR are located on a home network and an MS is located

on a common internet in accordance with a fourth embodiment of the present

invention.

MODES FOR CARRYING OUT THE PREFERRED EMBODIMENTS

15

Reference will now be made in detail to the preferred embodiments of the

present invention, examples of which are illustrated in the accompanying

drawings.

When some of UPnP devices exist on an internet, the UPnP devices can

20   interwork (operate) with each other by transforming a private address to a public

address by URI address transformation. Here, an MS and an MR that are

UPnP AV devices are located on different networks, and a CP for controlling the

UPnP AV devices is located on any one of a home network and a common

internet.

In accordance with the present invention, the UPnP AV device, the CP or

5   an Internet Gateway Device (IGD) for connecting the CP and the UPnP AV

device performs the URI address transformation.   The URI address

transformation implies transformation of an IP address and a port by Network

Address Transform (NAT).   In the case of an in-band streaming protocol, the

CP performs the URI address transformation, and in the case of an out-of-band

10   streaming protocol, the UPnP AV device performs the URI address

transformation, which is advantageous in the processing speed.

On the other hand, when the CP is located on the home network and

intends to control the UPnP AV device located on the common internet, it is

presumed that the CP knows a description address according to a well-known

15   address method or a dynamic Domain Name Service (DNS) method.   It is also

presumed that the CP accesses the UPnP AV device located on the common

internet by using the description address.   It is still presumed that the UPnP AV

device located on the common internet does not broadcast a search message

for UPnP addressing or discovery and does not respond to an M-search

20   message.   It is still presumed that, when the CP located on the home network

and the UPnP AV device located on the common internet are connected to each

other, the CP or the UPnP AV device performs port mapping.

Fig. 2 is a structure diagram illustrating a UPnP AV device control system in which a CP and an MR are located on a common internet, an MS is located on a home network, and an IGD for connecting the CP and the MS is included in

5   accordance with a first embodiment of the present invention.

As illustrated in Fig. 2, the MS 220 includes a UPnP IGD CP 221, and the IGD 240 connects the CP 210 located on the common internet and the MS 220 located on the home network. Here, the IGD 240 is an independent gateway device or a personal computer (PC) serving as a gateway.

10   The operation of the UPnP AV device control system in accordance with the first embodiment of the present invention will now be described.

The CP 210 located on the common internet is connected to the MS 220 through the IGD 240 by confirming a description address including a list on devices and services. In order to obtain an address of predetermined contents

15   from the MS 220, the CP 210 transmits Browse( ) or Search( ) action to the MS 220 through the IGD 240. The MS 220 transmits an action return value including a URI to the CP 210 through the IGD 240, and the CP 210 selects the MR 230 to play back the contents. Finally, when the contents are transmitted from the MS 220 to the MR 230 under the control of the CP 210, the MR 230

20   plays back the contents.

In order for the MR 230 located on the common internet to play back the

contents, a private address must be transformed to a fixed address. Such

address transformation is performed by transformation of the IP address and the

port by the NAT.

When the CP 210 located on the common internet and the MS 220

5   located on the home network are connected to each other, the NAT is set up by

the UPnP IGD CP 221 included in the MS 220. In addition, any one of the MS

220, the CP 210 and the IGD 240 for connecting the CP 210 and the MS 220

can perform the address transformation of the URIs included in the return values

of Browse( ) and Search( ) actions.

10   The URI address transformation can be performed on the whole URIs or

the URIs selected by the user (on-the-fly). Most preferably, the URI address

transformation is performed on the URIs selected by the user by the CP 210 in.

consideration of the processing speed. That is, in the case of an in-band

streaming protocol, the CP performs the URI address transformation, and in the

15   case of an out-of-band streaming protocol, the UPnP AV device performs the

URI address transformation, which is advantageous in the processing speed.

For example, it is presumed that the CP 210 selectively performs the URI

address transformation. When the user selects URI3, the CP 210 transforms

the address of the URI3, and the MR 230 streams the contents corresponding to

20   the address of the URI3 from the MS 220 by pulling. Here, the NAT port

mapping for out-of-band streaming has already been allocated by the MS 220.

Fig. 3 is a structure diagram illustrating a UPnP AV device control system

in which a CP and an MS are located on a home network and an MR is located

on a common internet in accordance with a second embodiment of the present

invention.

5   As shown in Fig. 3, the MS 320 includes a UPnP IGD CP 321, and an

IGD 340 connects the CP 310 located on the home network and the MR 330

located on the common internet.   Here, the IGD 340 is an independent gateway

device or a PC serving as a gateway.

The operation of the UPnP AV device control system in accordance with

10   the second embodiment of the present invention will now be described.

The CP 310 located on the home network confirms a description address

including a list on devices and services, and transmits Browse( ) action to the

MS 320 located on the home network to obtain an address of predetermined

contents.   The MS 320 transmits an action return value including a URI to the

15   CP 310.   The CP 310 selects the MR 330 located on the common internet to

play back the contents, and transmits SetAVTransportURI( ) action to the MR

330 through the IGD 340.

Finally, the MR 330 streams and plays back the contents from the MS

320.   Here, in order for the MR 330 located on the common internet to play

20   back the contents, the CP 310 located on the home network transforms a URI

address of the SetAVTransportURI( ) action into a fixed address.

The address transformation is performed by the NAT.   When the CP 310 located on the home network and the MS 320 located on the common internet are connected to each other, the NAT is .set up by the UPnP IGD CP 321 included in the MS 320.   As described in the first embodiment, the MS 320, the

5   IGD 340 or the CP 310 can perform the URI address transformation.   Also, the CP 310 can perform the address transformation on the URIs selected by the user.

Finally, the MR 330 streams the contents corresponding to the address of the URI transformed by the CP 310 from the MS 320 by pulling.   Here, the NAT

10   port mapping for out-of-band streaming has already been allocated by the MS 320.

Fig. 4 is a structure diagram illustrating a UPnP AV device control system in which a CP and an MS are located on a common internet and an MR is located on a home network in accordance with a third embodiment of the

15   present invention.

As depicted in Fig. 4, the MS 430 includes a UPnP IGD CP 431, and an IGD 440 connects the CP 410 located on the common internet and the MR 430 located on the home network.   Here, the IGD 440 is an independent gateway device or a PC serving as a gateway.

20   The operation of the UPnP AV device control system in accordance with the third embodiment of the present invention will now be described.

11

The CP 410 located on the common internet confirms a description address including a list on devices and services, and selects the MR 430 located on the home network through the IGD 440 as a device for playing back contents. When the CP 410 located on the common internet and the MR 430 located on

5 the home network are connected to each other, the NAT is set up to transform a private address to a fixed address by the UPnP IGD CP 431 included in the MR 430.

The CP 410 located on the common internet checks an address of contents of the MS 420 by confirming the previously-known description

10 information, and transmits Browse( ) action to the MS 420 to transmit the contents which the user intends to play back to the MR 430 located on the home network.

Finally, the MS 420 performs contents streaming to the MR 430 by pushing, so that the MR 430 can play back the corresponding contents. Here,

15 the action does not require any URI address transformation.

Fig. 5 is a structure diagram illustrating a UPnP AV device control system in which a CP and an MR are located on a home network and an MS is located on a common internet in accordance with a fourth embodiment of the present invention.

20 As illustrated in Fig. 5, the MS 530 includes a UPnP IGD CP 531, and an IGD 540 connects the CP 510 located on the home network and the MS 520

12

located on the common internet.   Here, the IGD 540 is an independent gateway device or a PC serving as a gateway.

The operation of the UPnP AV device control system in accordance with the fourth embodiment of the present invention will now be described.

5   -   The CP 510 located on the home network confirms a description address including a list on devices and services, and selects the MR 530 located on the home network as a device for playing back contents.   When the CP 510 and the MR 530 are connected to each other, the NAT is set up to transform a private address to a fixed address by the UPnP IGD CP 531 included in the MR

10   530.

The CP 510 located on the home network confirms an address of contents by the description information, and transmits SetAVTransportURI( ) action for selecting playback contents to the MS 520 through the IGD 540. Here, the URI address transformation of the SetAVTransportURI( ) action called

15   by the MS 520 is performed in the same manner as that of the first embodiment of the present invention.

Finally, the MS 520 performs contents streaming to the MR 530 by pushing, so that the MR 530 can play back the corresponding contents.

As discussed earlier, in accordance with the present invention, even if the

20   UPnP AV devices are located on the home network and the common internet, respectively, the UPnP AV devices can interwork with other.   As a result,

applications of the UPnP AV devices can be widely expanded at a low cost.

As the present invention may be embodied in several forms without departing from the spirit or essential characteristics thereof, it should also be understood that the above-described embodiments are not limited by any of the

5   details of the foregoing description, unless otherwise specified, but rather should be construed broadly within its spirit and scope as defined in the appended claims, and therefore all changes and modifications that fall within the metes and bounds of the claims, or equivalence of such metes and bounds are therefore intended to be embraced by the appended claims.